



## Superior board product suitable for premium packing applications

- A high bulking, stiff board suitable for a variety of premium carton solutions
- Suitable for chiller and freezer
- Certified for food packaging
- Stocked for next day delivery
- Available as a Reel Fast product

| Thickness | Weight           | Whiteness | Smoothness (T) | Stiffness |      |      |
|-----------|------------------|-----------|----------------|-----------|------|------|
| µm        | g/m <sup>2</sup> | CIE       | s              | MD        | CD   | GM   |
| 340       | 210              | 95        | 1.0            | 6.5       | 3.7  | 4.1  |
| 390       | 240              | 95        | 1.0            | 10.6      | 5.6  | 7.7  |
| 405       | 250              | 95        | 1.0            | 12.1      | 6.3  | 8.7  |
| 445       | 270              | 95        | 1.2            | 14.00     | 7.2  | 10.1 |
| 495       | 300              | 95        | 1.2            | 19.7      | 9.3  | 13.5 |
| 540       | 320              | 95        | 1.2            | 24.2      | 12.1 | 17.1 |
| 605       | 360              | 95        | 1.5            | 31.9      | 16.3 | 22.7 |

| Stock Range |                  |         |         |         |          |          |           |
|-------------|------------------|---------|---------|---------|----------|----------|-----------|
| µm          | g/m <sup>2</sup> | 450x640 | 520x720 | 640x900 | 720x1020 | 1020x720 | Reel Fast |
| 340         | 210              |         |         |         | ✓        | ✓        |           |
| 390         | 240              | ✓       | ✓       | ✓       | ✓        | ✓        | ✓         |
| 405         | 250              |         |         |         |          |          |           |
| 445         | 270              | ✓       | ✓       | ✓       | ✓        | ✓        | ✓         |
| 495         | 300              | ✓       | ✓       | ✓       | ✓        | ✓        | ✓         |
| 540         | 320              |         |         |         |          |          |           |
| 605         | 360              | ✓       | ✓       | ✓       | ✓        | ✓        | ✓         |

|     |                    |     |             |              |              |              |                  |                  |
|-----|--------------------|-----|-------------|--------------|--------------|--------------|------------------|------------------|
|     |                    |     |             |              |              |              |                  |                  |
| FSC | Carbon<br>Balanced | ECF | ISO<br>9001 | ISO<br>14001 | ISO<br>45001 | ISO<br>50001 | BfR<br>Compliant | FDA<br>Compliant |
|     | OPTION             |     |             |              |              |              |                  |                  |